

MORE SAFETY MORE POWER



TSUNESS Headquarter

www.tsun-ess.com
+86 512 6618 6028
sales@tsun-ess.com
2nd Floor, Building 2, No. 55 Aigehao Road, Weitang Town, Xiangcheng District, Suzhou City, Jiangsu Province, China

TSUNESS Europe GmbH

de.tsun-ess.com
sales@tsun-ess.com / service_DE@tsun-ess.com
Friedrich-Ebert-Anlage 36, 60325 Frankfurt am Main, Germany












EASY SOLAR KIT Balcony Angled

TSOL-ESK400-BA / TSOL-ESK800-BA



Applicable for
Balcony
Designed with a specific PV tilt angle,
ensuring high power output



 Solid	 Highly Waterproof	 Wind-resistant Snow-prevention
 Plug & Play	 All-in-one Design	 DIY Installation
 Built-in WiFi, APP Remote Monitoring	 Output Power 400W/800W Can be Adjusted According to Local Regulations	 Angle Adjustable for More Power Generation

TSUNESS Co., Ltd
sales@tsun-ess.com www.tsun-ess.com +86-512-66186028

Technical Data

Model	TSOL-ESK400-BA	TSOL-ESK800-BA
PV Module Parameter *		
Module Power(Pmpp @STC)	400 (400 - 460 optional)	400 * 2 (400 - 460 optional)
Max. Module Efficiency	20.7% (up to 24%)	20.7% (up to 24%)
Temp. Coef. (Power)	-0.34%/°C	-0.34%/°C
Color	Black	Black
AC Output Parameter		
Max. System Continuous Output Power (W)**	400	800
Max. Output Current (A)	2	4
Nominal Output Voltage (V)***	220/230/240	
Nominal Frequency (Hz)***	50/60	
Power Factor	>0.99	
Output Current Harmonic Distortion	<3%	
Length of AC End Cable***	5m (10m, 15m optional)	
Certification		
Solar Module	CE,TUV,UL,CQC,IEC 61215,IEC 61730	
Microinverter	CE-LVD,CE-EMC,CE-RED,VDE 4105,EN 50549-1	
Bracket	EN 10204:2017, EN 1090-1:2009+A1: 2011	
Environmental Parameter		
Environmental Protection Rating	IP67	
Operating Ambient Temperature Range	-25 °C to 65 °C	
Relative Humidity	0-100%	
Max. Operating Altitude Without Derating [m]	2000	
Mechanical Parameter		
Weight [kg]	29	58
Package Dimensions (W×H×D mm)	1722x1195x605	1722x1195x605 *2pcs
Color	S: Silver / B:Black / BC: Blakc Piemer (Back Contact PV module)	
Warranty	12 years	

* The colour , brand and power of the solar module can be customized if the PV module is compatible to ESK system.


** The output power of the system can be limited to 300W(ESK400) or 600W(ESK800).

*** The AC voltage , frequency range and plug type may vary depending on specific country grid.


Ordering Information

Model		
Balcony Angled	TSOL-ESK400-BA	TSUNESS ESK Balcony Angled (400W Full black panel, black bracket with fixed angle, micro inverter MS400, end cable 5m and plug)
Balcony Angled	TSOL-ESK800-BA	TSUNESS ESK Balcony Angled (400W Full black panel*2, black bracket with fixed angle*2, micro inverter MS800, DC cable 2m*2, end cable 5m and plug)


Standard Configuration



System Diagram



Monitoring Platform



Application



Talent Home is an **energy monitoring mobile application software**.

Users can use Talent Home to monitor the real-time operation of the entire pv power generation system.

Monitor Generation Data of Solar Plant

One-button to Connect Network

Power Generation Statistics

Module-level Monitoring System

Fast Network Configuration